CLARK FLUSHOMETER BOWL 4.8LPF / 1.28GPF | WALL HUNG

☐ 4762CEX Top Inlet ☐ 4762CEU Rear Inlet

PRODUCT SPECS

- High efficiency wall hung flushometer bowl
- 4.8Lpf / 1.28Gpf
- Will also function with 6Lpf / 1.6Gpf flushometer
- Elongated bowl
- Vitreous china
- 2" Fully glazed ball pass trapway
- Siphon jet flush action
- 11/2" Top or back inlet spud
- Water surface: 101/4" x 85/8" (260mm x 220mm)
- Toilet seat and flushometer not included

DIMENSIONS

390mm W x 650mm D x 335mm H 15%" W x 25½" D x 13%" H

COMPLIANCE CERTIFICATIONS

Meets or exceeds the following:

- IAPMO cUPC
- US EPA WaterSense
- ASME A112.19.2 / CSA B45.1
- ANSI A117.1 ADA Guideline
- Top Inlet: MaP tested 1000g
- Rear Inlet: MaP tested 600g
- NBC and OBC Section 3.8 Barrier Free design and CSA B651 Standard.
- LEED Compliant

SHIPPING

Cube 3.79 GW 50 lbs





NOTES: Toilet models designed to meet ADA Accessibility Standard when top of seat at 432mm to 482mm (17" to 19") from finished floor. Flush valve not included with fixture and must be ordered separately. Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

