

Features

- For baths 14" (356 mm) to 21" (533 mm) deep from the center of the bath overflow outlet to the center of the bath drain outlet
- External 27" (686 mm) length cable
- No internal linkages to minimize the potential for clogging
- Includes schedule 40 PVC tubing

Material

- Metal construction control handle and stopper

Installation

- Adjustable rotating connection for easy installation

Recommended Products/Accessories

- K-23726 Drain treatment
- K-23723 Faucet cleaner



Codes/Standards










ASME A112.18.2/CSA B125.2
IAPMO Certification


KOHLER[®] One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	PB	Vibrant [®] Polished Brass
	BN	Vibrant [®] Brushed Nickel
	BV	Vibrant [®] Brushed Bronze
	2BZ	Oil-Rubbed Bronze
	BL	Matte Black
	2MB	Vibrant [®] Brushed Moderne Brass
	RGD	Vibrant Rose Gold
	TT	Vibrant Titanium



Technical Information

All product dimensions are nominal.

Drain included: Yes

Notes

Install this product according to the installation guide.

The combined length of the vertical (supplied) and horizontal (supplied) tubing after being cut for the bath installation must be equal to or less than 25" (635 mm).