

# Composed™

Sliding shower door K-701695-L

#### **Features**

- Sleek, exposed roller design allows for effortless opening and closing of the sliding panel
- Frameless design emphasizes glass and creates a sleek, minimalist look
- Controlled Close® innovative soft-close with doubledampening technology eliminates slamming and brings door to a secure close
- Back-to-back 11-1/2" (292 mm) vertical handles
- CleanCoat®+ glass coating creates a hydrophobic barrier that repels water, soap scum, and residue, saving time and protecting shower doors 10 times longer than original CleanCoat. (Based on 2021 internal wear/abrasion testing using a microfiber cloth.)
- Coordinates with other products in the Composed® collection

#### Material

- Frameless, heavy 3/8" (10 mm) thick Crystal Clear tempered glass door and in-line panel
- Anodized aluminum prevents rust and corrosion

### Installation

- 78" (1981 mm) high, with a lofty 74-7/8" (1902 mm) minimum head clearance
- Fits opening widths 44-1/8" 47-7/8" (1121 –1216 mm)
- 3-3/4" (95.25 mm) width adjustment
- Out-of-plumb adjustability simplifies installation
- Door can be installed to open to the left or right to suit your bathroom layout
- For residential use only
- Not for use in hospitality
- Not for use with cast iron shower bases

### **Recommended Products/Accessories**

K-23723 Faucet cleaner



### Codes/Standards

ANSI Z97.1 CAN/CGSB-12.1 CPSC 16CFR 1201

# **KOHLER® Bath and Shower Doors Ten-Year Limited Warranty**

See website for detailed warranty information.

## **Available Colors/Finishes**

Color tiles intended for reference only.

Color	Code	Description
	SHP	Bright Polished Silver
1	BNK	Anodized Brushed Nickel
	BL	Matte Black

# Available Glass Options

Code Description


L Crystal Clear






# Composed™

Sliding shower door K-701695-L





## \*Walk-through

## **Notes**

The vertical opening should be a minimum of 80" (2032 mm) to allow for installation clearance.

## **Technical Information**

All product dimensions are nominal.

Base-To-Wall 3/8" (10 mm)

Radius – Max:

