

# Sliding bath door, 56-3/4" H x 56-1/4 - 59-5/8" W

## K-707618-8G79

#### **Features**

- Frameless design emphasizes glass and creates a sleek, minimalist look
- Vertical handle with inside knob on moving panel
- Gently-curved towel bar provides integrated storage on fixed panel
- Tempered glass ensures enhanced safety and durability
- CleanCoat®+ glass coating creates a hydrophobic barrier that repels water, soap scum, and residue, saving time and protecting shower doors 10 times longer than original CleanCoat. (Based on 2021 internal wear/abrasion testing using a microfiber cloth.)
- Smooth, easy-to-clean wall jambs
- Full-length moving panel seal provides excellent water containment
- Coordinates with other products in the Elate collection
- Shower door configuration consists of one sliding panel and one stationary panel

#### Material

- Frameless, heavy 5/16" (8 mm) thick Crystal Clear tempered glass with easy-to-clean rectangular grille design imprinted on surface
- Anodized aluminum prevents rust and corrosion

#### Installation

- Fits opening widths 56-1/4" 59-5/8" (1429 1514 mm)
- 3-3/8" (86 mm) width adjustment
- Out-of-plumb adjustability simplifies installation
- Door can be installed to open to the left or right to suit your bathroom layout
- For residential use only
- Not for use in hospitality



#### Codes/Standards

ANSI Z97.1 CAN/CGSB-12.1 CPSC 16CFR 1201

## **KOHLER® Bath and Shower Doors Ten-Year Limited Warranty**

See website for detailed warranty information.

## Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

BL Matte Black

## **Available Glass Options**


**Code Description** 

Crystal Clear with Rectangular G79

Grille Pattern



## Sliding bath door, 56-3/4" H x 56-1/4 - 59-5/8" W K-707618-8G79



#### **Technical Information**

All product dimensions are nominal. 1/2" (13 mm) Base-To-Wall Radius - Max:

## **Notes**

Install this product according to the installation instructions.

The vertical opening should be a minimum of 60-1/8" (1527 mm) to allow for installation clearance.

