

Features

- Freestanding design creates a striking focal point in your bathing area
- Rectangular basin creates a spacious bathing experience
- Integral lumbar support on both ends
- Slotted overflow allows for deep soaking
- 12-1/16" (306 mm) deep-soaking depth provides a luxurious bathing experience
- Safeguard® slip-resistant surface provides excellent traction underfoot
- Center drain
- Drain and integral overflow preinstalled to reduce installation time
- Color-matched pedestal base creates a sleek appearance
- Requires K-36361 Volute bath drain trim (sold separately)

Material

- KOHLER® enameled cast iron bath
- Painted exterior in Iron Black
- Reinforced resin pedestal base with Iron Black painted finish
- Brass drain

Installation

- Freestanding

Required Products/Accessories

For freestanding installation
K-36361 Bath drain trim



Codes/Standards

ASME A112.19.1/CSA B45.2

KOHLER® Enameled Cast Iron Bath and Shower Base Lifetime Limited Warranty


See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

| Color | Code | Description |
|-------|------|-------------|
|-------|------|-------------|

| | | |
|---|---|-------|
|  | 0 | White |
|---|---|-------|



Technical Information

All product dimensions are nominal.

| | |
|---------------------|---|
| Drain location: | Center |
| Basin area, bottom: | 50-5/16" x 20-3/8" (1278 mm x 518 mm) |
| Basin area, top: | 60-1/4" x 23-11/16" (1531 mm x 602 mm) |
| Weight: | 338 lbs (153.3 kg) |
| Minimum floor load: | 60.2 lbs/ft ² (293.9 kg/m ²) |
| Water depth: | 12-1/8" (308 mm) |
| Water capacity: | 45.97 gal (174 L) |

Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.