# Touchless faucet w/Kinesis® sensor, AC-powered K-103K36-SANA

#### **Features**

- Kinesis® technology with concealed sensor allows for a clean aesthetic and provides extraordinarily accurate and reliable actuation in varying installation environments
- Below-counter valving reduces the faucet footprint and provides easier service
- Design-forward aesthetic for commercial bathroom spaces
- 0.5 gpm (1.9 lpm) maximum flow rate
- Requires K-13480 single or K-13481 multiple AC adapter unit
- On-demand usage with 30-second max. continual run cycle to prevent vandalism and save water
- Vandal-resistant aerator
- 18" (457 mm) stainless steel braided flexible supply hose for easy installation
- 5-5/16" (135 mm) spout reach
- Grid drain
- Concealed mechanical mixer sold separately
- Complies with the Safe Drinking Water Act (SDWA)
- Includes spout assembly, grid drain, control box assembly, supply hose, and standard mounting hardware

#### Material

- Metal construction spout
- Cast brass valve

### **Technology**

 Kinesis® sensor technology offers on-demand detection for maximum water savings

#### Installation

Single-hole mounting

### **Required Products/Accessories**

K-13480 AC Single Supply

or

K-13480-A AC Single Supply

or

K-13481 Multi-Outlet Power Supply

or

K-13481-A Multi-Outlet Power Supply

#### **Recommended Products/Accessories**

K-23726 Drain treatment K-23723 Faucet cleaner

## **Optional Products/Accessories**

K-99799 Thermostatic Tempering Valve K-13478-A 4" escutcheon plate for Insight™ and Kinesis®

faucet
K-13478-B 4" escutcheon plate for Insight™ and Kinesis®

1-800-4KOHLER (1-800-456-4537)



ADA CSA B651 OBC

#### Codes/Standards

ASME A112.18.1/CSA B125.1 NSF/ANSI/CAN 61

NSF/ANSI/CAN 372

All applicable US Federal and State material regulations

DOE - Energy Policy Act 1992

California Energy Commission (CEC)

ADA

ICC/ANSI A117.1

CSA B651

OBC

**IAPMO** Certification

# KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

#### **Available Colors/Finishes**


Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	BN	Vibrant® Brushed Nickel
	BL	Matte Black
	2MB	Vibrant® Brushed Moderne Brass



# **Kumin®**

# Touchless faucet w/Kinesis® sensor, AC-powered K-103K36-SANA



## **Required Electrical Service**

## **Technical Information**

All product dimensions are nominal.

Power source: Hardwire - AC and Plug - AC, not

included

Faucet:

Flow rate: 0.5 gal/min (1.9 l/min)

Pressure: 60 psi (4.1 bar)

Drain included: Yes

Spout:

Spout reach: 5-5/16" (135 mm)

#### **Notes**

Install this product according to the installation instructions.

A 1-1/4" (32 mm) minimum to 1-1/2" (38 mm) maximum diameter mounting hole is required.

The minimum distance between the back of the faucet spout and the wall must be 1-3/4" (44 mm). This will allow proper clearance for setscrew access.

The maximum distance between the bathroom sink basin edge to the base of the faucet spout must be 1-3/4" (44 mm).

This product requires an AC power supply (not included).

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

