


The Next Necessity^{*}



Dimensions



Instant Hot Water Dispensers



H-Classic-SS

Easy-grip handle to dispense instant near-boiling 200°F water effortlessly

Submittal Sheet

- Hot Only Dispenses near-boiling 200°F water
- Includes 2/3-gallon hot water tank
- Easy to adjust temperature control
- Tool-free tank connections and dry start protection to ease installation
- Provides 60 cups/hr of near-boiling water
- We Come To You® 3-Year In-Home Limited Warranty*
- 115 volts, 750 watts, 6.5 amps
- Available in chrome
- Unit not for commercial/industrial use

Specifications

Capacity	2/3-gallon hot water tank dispenses 60 cups of 200°F water per hour
lectrical	115 volts A.C., 750 watts, 6.5 amp heating element with grounded three (3) prong plug
hermostat	Snap-action, adjustable from 160°F to 210°F (factory pre-set at 200°F)
nsulation	Meets U.L. 94HF-1 flammabiltiy specification
/alve	Instant, self-closing
Recommended Supply Pressure	30-80 psi
hipping Weight	Approximately 7.4 lbs.
Required Iole Diameter	1-3/8" standard sink hole
	lectrical hermostat hsulation alve ecommended upply Pressure hipping Weight eequired

Sample Specification

Instant hot water dispenser(s) shall be InSinkErator Model H-Classic-SS with 2/3-gallon hot water tank, adjustable temperature from 160°F to 210°F and instant, self-closing hot valve.

Warranty:

3-year parts and in-home service.

* The complete InSinkErator warranty is included in the Care & Use booklet packed with each unit.

US Patent Pending (tank enclosure)

Job Specifications



Complies with California Lea Plumbing Law

USA 1-800-558-5700 www.insinkerator.com

Canada 1-800-558-5700 www.insinkerator.ca

InSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models.

Printed in USA

Water Filtration

System Available