



60" x 36" alcove whirlpool bath Bask® heated surface, right drain

K-1239-RAW

#### **Features**

- Bask® heated surface creates spa-like relaxation with soothing warmth on your back, shoulders, and neck
- Three heat settings allow you to customize the surface temperature
- Single-speed whirlpool offers performance and value, with 5 fully adjustable jets
- Hydromassage flow and direction can be controlled at each iet
- Hourglass shape adds style and elegance to your bathroom
- Integral apron
- Integral flange helps prevent water from seeping behind wall and simplifies alcove installation
- Textured bottom surface

### Material

Acrylic

# **Hydrotherapy**

Whirlpool

# Installation

- Right drain
- Alcove

## Required Products/Accessories

K-T37391 Rotary-turn bath drain trim K-T37392 Rotary-turn bath drain trim

or

K-37383 Rough-in cable bath drain, PVC, 30" cable with tubing

K-78438 30" cable bath drain

or

K-37385 rough-in cable drain, PVC, 45" cable K-78439 45" cable bath drain

#### **Recommended Products/Accessories**

K-9695 5-Jet Trim Kit K-23726 Drain treatment K-23732 Tub & shower cleaner K-7265 Brass toe tap bath drain K-7259 Brass toe tap bath drain K-31796 Above-the-floor bath drain kit K-31798 Bath drain kit



## Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 IAPMO Certification UL Listed

# KOHLER® Plastic Baths and Shower Bases Lifetime Limited WarrantyKOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

## Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit









60" x 36" alcove whirlpool bath Bask® heated surface, right drain


K-1239-RAW


No change in measurements if connected with drain illustrated. (K-7161-AF)

Recommended Faucet Location









# **Required Electrical Service**

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Pump, Heated 120 V, 15 A, 60 Hz

Surface:

## **Technical Information**

All product dimensions are nominal.

Drain location: Right

Basin area, bottom: 46" x 24" (1168 mm x 610 mm) Basin area, top: 54" x 27" (1372 mm x 686 mm)

Weight: 111 lbs (50.3 kg)
Minimum floor load: 44 lbs/ft² (214.8 kg/m²)

Water depth: 14" (356 mm)
Water capacity: 63 gal (238.5 L)

Electrical component Pump: 120 V, 7 A, 60 Hz

rating: Heated Surface: 120 V, 0.5 A, 60 Hz, 65

W

Pump speed: Single

#### **Notes**

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference above or below the deck before drilling any holes.

